



## D25481K-B5

40MM SDS Max Combination Hammer w/  
AVC 5Kg 220V

### FEATURES

- Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 40 mm in diameter. Core drilling up to 90 mm
- Chain drive improves durability and increases efficiency together with an oil filled gearbox to ensure total component lubrication and superior heat dissipation
- Ergonomic, compact and slim line design maximizes control and offers easy access to confined spaces
- Excellent power to weight ratio: 8 Joules of impact energy delivered by a 6.1 kg hammer
- Rotation-stop for medium-light demolition applications
- Unique dust sealing protection to prevent even the finest dust ingress into the hammer mechanism delivering high durability and extended tool life
- Hammer mechanism is optimized by reducing the number of components and by improving dampening to deliver maximum impact energy and therefore the efficiency to drill into the hardest concrete
- Efficient mechanism delivers impact blows directly to the bit without losses through excessive vibration and rebound dampening reduces stress to the tool
- Soft rubber grip handles improve user comfort lowering fatigue during extended use

### SPECIFICATIONS

|                              |            |
|------------------------------|------------|
| Tool Holder                  | SDS-Max    |
| Power Input                  | 1100 Watts |
| Power Output                 | 500 Watt   |
| Impact energy (EPTA 05/2009) | 8 J        |
| Load Speed                   | 400 rpm    |
| Blows per Minute             | 2740 bpm   |

|  |                       |
|--|-----------------------|
| Max. Drilling Capacity [Concrete]                  | 40 mm                 |
| Max. Drilling Capacity [Breakthrough bit]          | 55 mm                 |
| Max. Drilling Capacity [Core bit]                  | 90 mm                 |
| Weight   | 6.1 kg                |
| Length   | 457 mm                |
| Height   | 245 mm                |
| Width  | 104 mm                |
| Hand/Arm Vibration - Hammer drilling into concrete | 18.3 m/s <sup>2</sup> |
| Uncertainty K 1 (Vibration)                        | 1.8 m/s <sup>2</sup>  |
| Hand/Arm Vibration - Chiseling                     | 13.2 m/s <sup>2</sup> |
| Uncertainty K 2 (Vibration)                        | 1.6 m/s <sup>2</sup>  |
| Sound Pressure                                     | 94 dB(A)              |
| Sound Pressure Uncertainty                         | 3 dB(A)               |
| Sound Power  | 104 dB(A)             |
| Sound Power Uncertainty                            | 3 dB(A)               |