



## D25601K-GB

45mm SDS Max Combination Hammer 6Kg  
220V

### FEATURES

- Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 45 mm in diameter. Core drilling up to 100 mm
- Chain drive improves durability and increases efficiency together with an oil filled gearbox to ensure total component lubrication and superior heat dissipation
- Active vibration control system incorporating a floating rear handle and damped side handle to reduce vibration
- Ergonomic, compact and slim line design maximizes control and offers easy access to confined spaces
- Rotation-stop for medium-light demolition applications
- Unique dust sealing protection to prevent even the finest dust ingress into the hammer mechanism delivering high durability and extended tool life
- Hammer mechanism is optimized by reducing the number of components and by improving dampening to deliver maximum impact energy and therefore the efficiency to drill into the hardest concrete
- Efficient mechanism delivers impact blows directly to the bit without losses through excessive vibration and rebound dampening reduces stress to the tool
- Soft rubber grip handles improve user comfort lowering fatigue during extended use
- Electronic variable impact energy/speed for total control with smaller bits and light material
- Lock-on switch for greater control when in chipping mode
- Electronic service and brush wear indicator identifies when brushes need replacing and product should be serviced
- Excellent power to weight ratio: 8 Joules of impact energy delivered by a 6.8 kg hammer.
- Magnesium housing for lower weight and excellent durability

### SPECIFICATIONS

Tool Holder	SDS-Max
Power Input	1250 Watts
Power Output	615 Watt
Impact energy (EPTA 05/2009)	8 J
Load Speed	210-415 rpm

Blows per Minute	1430-2840 bpm
Max. Drilling Capacity [Concrete]	45 mm
Max. Drilling Capacity [Breakthrough bit]	65 mm
Max. Drilling Capacity [Core bit]	100 mm
Weight	6.8 kg
Length	477 mm
Height	245 mm
Width	104 mm
Hand/Arm Vibration - Hammer drilling into concrete	8.8 m/s <sup>2</sup>
Uncertainty K 1 (Vibration)	1.5 m/s <sup>2</sup>
Hand/Arm Vibration - Chiseling	7.2 m/s <sup>2</sup>
Uncertainty K 2 (Vibration)	1.5 m/s <sup>2</sup>
Sound Pressure	92 dB(A)
Sound Pressure Uncertainty	3 dB(A)
Sound Power	103 dB(A)
Sound Power Uncertainty	3 dB(A)